

GENERAL NOTES

The maximum spacing between channelizing devices in a taper should be 12m; the maximum spacing between channelizing devices used to separate traffic should be 25m.


Channelizing devices shall be a minimum of 0.7m in height.

Traffic safety drums shall be used for channelization devices during nighttime operations. (See Special Provisions)

LEGEND

- ▣ ▣ ▣ CHANNELIZING DEVICES
- ◀ SIGN

TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES FOR FREEWAY/EXPRESSWAY ON-RAMP AND LANE CLOSURE.

				REGION NO.	STATE	FED.AID PROJ.NO.	ENVIRONMENTAL AND ENGINEERING SERVICE CENTER	 Washington State Department of Transportation	SR 5 NEWAUKUM RIVER BRIDGE TO THURSTON COUNTY LINE	REFERENCE SHEET NUMBER
DESIGNED BY	B. McMULLEN			10	WASH	IM-0051(236)				
ENTERED BY	W. CASEY									
CHECKED BY	D. HOKANSON									
PROJ. ENGR.	T. PASELK									
DIST. ADM.	G. E. SMITH									
	DATE	DATE	REVISION	RY				o:\dgn\12738tr-f.dgn	31 JAN 97	TRAFFIC CONTROL PLAN